

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

ORIGINAL

FIELD NOTES
OF
THE DEPENDENT RESURVEY OF
THE NORTH BOUNDARY (SECOND STANDARD PARALLEL SOUTH),
A PORTION OF THE SUBDIVISIONAL LINES
AND
A PORTION OF MINERAL SURVEY NO. 6997
IN SECTIONS 1 AND 2
AND THE
SUBDIVISION OF SECTIONS 3, 5, 13, 16, 21, 22, AND 35
IN
TOWNSHIP 11 SOUTH, RANGE 3 WEST
OF THE SALT LAKE MERIDIAN
IN THE STATE OF UTAH

EXECUTED BY

Jerry L. Thomas
Cadastral Surveyor

Under special instructions dated *August 9, 1999*, approved *August 9, 1999*, which provided for the surveys included under Group Number *904*, and assignment instructions dated *September 7, 1999*

Survey commenced *September 21, 1999*
Survey completed *November 3, 1999*

INDEX DIAGRAM

Township 11 South, Range 3 West

7	6	5	4	3	2
6	41 5	35 4	29 3	23 2	16 1
40	40	34	29	22	
7	39 8	34 9	28 10	22 11	15 12
39	39	33	27	21	14
18	38 17	33 16	27 15	20 14	13 13
37	37	32	26	20	12
19	36 20	31 21	25 22	19 23	11 24
	35	31	25	18	11
30	29	30 28	24 27	18 26	10 25
			23	17	9
31	32	33	34	16 35	8 36

Subdivision of Section 3.....	Page 42
Subdivision of Section 5.....	Page 42
Subdivision of Section 13.....	Page 44
Subdivision of Section 16.....	Page 45
Subdivision of Section 21.....	Page 46
Subdivision of Section 22.....	Page 47
Subdivision of Section 35.....	Page 48
Dependent Resurvey, Portion of Mineral Survey No. 6997.....	Page 49

TOWNSHIP 11 SOUTH, RANGE 3 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

The plat for T. 11 S., R. 3 W., SLM, dated February 19, 1873 and the Supplemental Plat for T. 11 S., R. 3 W., SLM, dated December 2, 1905, depict the closing corners for sections 2 and 3, 4 and 5, 5 and 6, and the closing corner of sections 1 and 6, Tps. 11 S., Rs. 3 and 4 W., SLM, are platted easterly of the standard corners on the Second Standard Parallel South. The original field note record of T. 11 S., R. 3 W., SLM, dated February 19, 1873, describe the above closing corners being westerly of the standard corners. Corners found within the scope of the resurvey confirm the bearings and distances in the original field note record of T. 11 S., R. 3 W., SLM, dated February 19, 1873. This dependent resurvey and monuments set within these field notes are based on the original field note record for T. 11 S., R. 3 W., SLM, dated February 19, 1873.

The following field notes describe the dependent resurvey of the north boundary, (Second Standard Parallel South), a portion of the subdivisional lines and a portion of Mineral Survey No. 6997, in sections 1 and 2, and the subdivision of sections 3, 5, 13, 16, 21, 22, and 35, in Township 11 South, Range 3 West, Salt Lake Meridian, Utah.

History of Surveys

Surveyed by			Retr. or Resurveyed by	
SOUTH BOUNDARY				
All	J. Gorlinski	1872		
All			J.L. Thomas	1996-97
EAST BOUNDARY				
All	J. Gorlinski	1872		
Portion			H.D. Heist	1903
Portion			J.L. Thomas	1987-90
WEST BOUNDARY				
All	J. Gorlinski	1872		
All			G.B. Hatch	1968
NORTH BOUNDARY (Second Standard Parallel South)				
All	J. Gorlinski	1872		
Portion			G.B. Hatch	1966
Portion			M. Krohn	1987-88
SUBDIVISION				
All	J. Gorlinski	1872		
Portion			J.L. Thomas	1996-97
MINERAL SURVEY NO. 6997				
Portion	A.A. Miller	1929		

TOWNSHIP 11 SOUTH, RANGE 3 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

This survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. 904, Utah, dated August 9, 1999.

The distances and directions of lines were determined by the Global Positioning System, using relative positioning techniques.

The geographic position of Triangulation Station "CAPPS" as published by the National Geodetic Surveys, is as follows:

Latitude 39° 39' 43.87548" N. Longitude 112° 02' 47.39982" W.
NAD 1983 (1994) Elevation 5656 FT.

The geographic position of the corner of sections 1, 2, 35, and 36, on the south boundary of the township, is as follows:

Latitude 39° 48' 58.320" N. Longitude 112° 08' 18.505" W.
NAD 1983 Elevation 5902 FT.

The mean magnetic declination as projected from U. S. Geological Survey "Magnetic Declination Map of 1990" is 14° East.

Dependent Resurvey of the North Boundary
(Second Standard Parallel South),
T. 11 S., R. 3 W., Salt Lake Meridian, Utah

Reestablishment of the Survey Executed by
J. Gorlinski in 1872

From the standard corner of Tps. 10 S., Rs. 2 and 3 W., sections 31 and 36, on the Second Standard Parallel South, monumented with a trachyte stone, 17x12x6 inches, plainly marked with 6 notches on the N edge only.

At the corner point

Set an aluminum post, 30 inches long, 2 ½ inches diameter, 24 inches in the ground, with aluminum cap marked:

T10S
R3W R2W
S36 | S31
1999

Deposit the marked stone alongside the aluminum post.

Raise a mound of stone, 3 ft. base, 2 ft. high, north of the corner.

DEPENDENT RESURVEY OF THE NORTH BOUNDARY
(SECOND STANDARD PARALLEL SOUTH)
T. 11 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

N. $89^{\circ} 43.4'$ W., along the south boundary of section 36.

- 0.538** The closing corner of Tps. 11 S., Rs. 2 and 3 W., sections 1 and 6, monumented with a sandstone, 20x5x5 inches, firmly set, projecting 14 inches above ground, plainly marked with 6 notches on the S edge only.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T10S
S36
—
S1 | S6
C C
R3W R2W
T11S
1999

Deposit the marked stone alongside the aluminum post.

Raise a mound of stone, 3 ft. base, 2 ft. high, south of the corner.

- 40.415** The standard 1/4 section corner of section 36, monumented with a stainless steel post, 2 1/2 inches diameter, firmly set, projecting 6 inches above ground, with brass cap marked as described in the official record of the 1987-88 resurvey of a portion of the south boundary of T. 10 S., R. 3 W.

N. $89^{\circ} 33.7'$ W., beginning new measurement.

- 40.374** Point for the standard corner of sections 1, 2, 35, and 36, at proportionate distance, falls in paved surface of old abandoned road; there is no remaining evidence of the original corner.

At this point, set a railroad spike, flush with surface of road.

from which

An aluminum post, 30 inches long, 2 1/2 inches diameter, set over a magnet, 24 inches in the ground, for a reference monument, bears S. $60^{\circ} 43.8'$ W., 1.425 chains distance (94 ft.), with an aluminum cap marked T11S R3W S2 RM 1999 and an arrow pointing to the corner.

N. $89^{\circ} 33.7'$ W., on the south boundary of section 35.

Over nearly level land.

- 2.000** Center line of U.S. Highway No. 6, on a curve bears northwest and southeast.

DEPENDENT RESURVEY OF THE NORTH BOUNDARY
(SECOND STANDARD PARALLEL SOUTH)
T. 11 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS**40.374**

Point for the standard 1/4 section corner of section 35, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, over a magnet, 24 inches in the ground, with aluminum cap marked:

SC
T10S R3W
1/4 S35
1999

40.929

Point for the 1/4 section corner of section 2 only, north boundary, T. 11 S., R. 3 W., at midpoint between the corner of sections 1, 2, 35, and 36, and the closing corner of sections 2 and 3.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, over a magnet, 24 inches in the ground, with aluminum cap marked:

1/4 S2
T11S R3W
1999

Set a steel fence post alongside the corner.

80.748

The standard corner of sections 34 and 35, monumented with a stainless steel post, 2 1/2 inches diameter, firmly set, projecting 4 inches above ground, with brass cap marked as described in the official record of the 1987-88 resurvey of a portion of the south boundary of T. 10 S., R. 3 W.

Reestablishment of the Survey Executed by
J. Gorlinski in 1872 and the Resurvey by M. Krohn in 1987-88

S. 89° 39.7' W., on the south boundary of section 34, T. 10 S., R. 3 W.

Over gentle rolling land.

1.110

Point for the closing corner of sections 2 and 3, T. 11 S., R. 3 W., at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, over a magnet, 24 inches in the ground, with aluminum cap marked:

T10S
S3 | S2
C | C
T11S R3W
1999

Set a steel fence post alongside the corner.

DEPENDENT RESURVEY OF THE NORTH BOUNDARY
(SECOND STANDARD PARALLEL SOUTH)
T. 11 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS**20.189**

The E 1/16 section corner of section 34, monumented with a stainless steel post, 2 1/2 inches diameter, firmly set, projecting 4 inches above ground, with brass cap marked as described in the official record of the 1987-88 resurvey of a portion of the south boundary of T. 10 S., R. 3 W.

S. 89° 39.8' W., beginning new measurement.

20.177

The standard 1/4 section corner of section 34, monumented with a stainless steel post, 2 1/2 inches diameter, firmly set, projecting 4 inches above ground, with brass cap marked as described in the official record of the 1987-88 resurvey.

N. 89° 54.3' W., beginning new measurement.

0.023

Point for the 1/4 section corner of section 3 only, T. 11 S., R. 3 W., at midpoint between the closing corners of sections 2 and 3, and the corner of sections 3, 4, 33, and 34.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, over a magnet, 24 inches in the ground, with aluminum cap marked:

1/4 S3
T11S R3W
1999

19.655

The W 1/16 section corner of section 34, monumented with a stainless steel post, 2 1/2 inches diameter, firmly set, projecting 4 inches above ground, with brass cap marked as described in the official record of the 1987-88 resurvey.

N. 89° 54.9' W., beginning new measurement.

19.646

The standard corner of sections 3, 4, 33, and 34, monumented with a stainless steel post, 2 1/2 inches diameter, firmly set, projecting 4 inches above ground, with brass cap marked as described in the official record of the 1987-88 resurvey.

N. 89° 37.6' W., on the south boundary of section 33.

41.085

Point for the 1/4 section corner of section 4 only, T. 11 S., R. 3 W., at midpoint between the corner of sections 3, 4, 33, and 34, and the closing corner of sections 4 and 5.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, over a magnet, 24 inches in the ground, with aluminum cap marked:

DEPENDENT RESURVEY OF THE NORTH BOUNDARY
(SECOND STANDARD PARALLEL SOUTH)
T. 11 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

1/4 S4
T11S R3W
1999

Set a steel fence post alongside the corner.

Over gentle rolling land.

- 41.144** The standard 1/4 section corner of section 33, monumented with a stainless steel post, 2 1/2 inches diameter, firmly set, projecting 4 inches above ground, with brass cap marked as described in the official record of the 1987-88 resurvey.

N. 89° 48.0' W., beginning new measurement.

- 40.370** The standard corner of sections 32 and 33, monumented with a stainless steel post, 2 1/2 inches diameter, firmly set, projecting 4 inches above ground, with brass cap marked as described in the official record of the 1987-88 resurvey.

N. 89° 48.3' W., on the south boundary of section 32.

Over rolling land.

- 0.656** Point for the closing corner of sections 4 and 5, T. 11 S., R. 3 W., at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, over a magnet, 24 inches in the ground, with aluminum cap marked:

T10S
S32
S5 | S4
C | C
T11S R3W
1999

Set a steel fence post alongside the corner.

- 40.372** The standard 1/4 section corner of section 32, monumented with a stainless steel post, 2 1/2 inches diameter, firmly set, projecting 4 inches above ground, with brass cap marked as described in the official record of the 1987-88 resurvey.

N. 89° 36.4' W., beginning new measurement.

- 0.843** Point for the 1/4 section corner of section 5 only, north boundary, T. 11 S., R. 3 W., at midpoint between the closing corners of sections 4 and 5, and sections 5 and 6.

DEPENDENT RESURVEY OF THE NORTH BOUNDARY
(SECOND STANDARD PARALLEL SOUTH)
T. 11 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, over a magnet, 24 inches in the ground, with aluminum cap marked:

1/4 S5
T11S R3W
1999

Set a steel fence post alongside the corner.

- 40.187** The standard corner of sections 31 and 32, monumented with a stainless steel post, 2 1/2 inches diameter, firmly set, projecting 4 inches above ground, with brass cap marked as described in the official record of the 1987-88 resurvey.

N. 89° 44.1' W., on the south boundary of section 31.

Over rolling land.

- 1.213** Point for the closing corner of sections 5 and 6, T. 11 S., R. 3 W., at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, over a magnet, 24 inches in the ground, with aluminum cap marked:

T10S
S31
S6 | S5
C | C
T11S R3W
1999

Set a steel fence post alongside the corner.

- 40.429** The standard 1/4 section corner of section 31, monumented with a stainless steel post, 2 1/2 inches diameter, firmly set, projecting 4 inches above ground, with brass cap marked as described in the official record of the 1987-88 resurvey of a portion of the south boundary of T. 10 S., R. 3 W.

N. 89° 44.1' W., beginning new measurement.

- 1.199** Point for the 1/4 section corner of section 6 only, north boundary, T. 11 S., R. 3 W., at proportionate distance between the closing corners of sections 5 and 6, and closing corner of T. 11 S., Rs. 3 and 4 W.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, over a magnet, 24 inches in the ground, with aluminum cap marked:

DEPENDENT RESURVEY OF THE NORTH BOUNDARY
(SECOND STANDARD PARALLEL SOUTH)
T. 11 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

1/4 S6
T11S R3W
1999

Set a steel fence post alongside the corner.

- 40.428** The standard township corner of T. 10 S., Rs. 3 and 4 W., monumented with a stainless steel post, 2 1/2 inches diameter, firmly set, projecting 6 inches above mound of stone, with brass cap marked as described in the official record of the 1966 resurvey of a portion of the south boundary of T. 10 S., R. 4 W.

Reestablishment of the Survey Executed by
J. Gorkinski in 1872 and the Resurvey by G. Hatch in 1966

S. 89° 53.1' W., on the south boundary of section 36, T. 10 S., R. 4 W.

Over rolling land.

- 1.368** The closing township corner of T. 11 S., Rs. 3 and 4 W., monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 6 inches above ground, with brass cap marked as described in the official record of the 1966 resurvey.

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 11 S., R. 3 W., Salt Lake Meridian, Utah

Reestablishment of the Survey Executed by
J. Gorkinski in 1872

From the corner of sections 1, 2, 35, and 36, south boundary, monumented with an aluminum post, 2 1/2 inches diameter, firmly set, projecting 6 inches above ground, with aluminum cap marked as described in the official record of the 1996-97 resurvey of a portion of the north boundary of T. 12 S. R. 3 W.

N. 0° 33.5' E., between sections 35 and 36.

Over rolling land.

- 40.560** The 1/4 section corner of sections 35 and 36, monumented with a limestone 12x12x6 inches, firmly set, projecting 6 inches above ground, marked 1/4 on the west face.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, over a magnet, 24 inches in the ground, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 11 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

T11S R3W
1/4
S35 | S36
1999

Deposit the marked stone alongside the aluminum post.

Set a steel fence post alongside the corner.

Corner is located in a N and S fence line.

N. 1° 32.2' E., beginning new measurement.

40.291 The corner of sections 25, 26, 35, and 36, monumented with a porphyry stone 12x10x10 inches, firmly set, projecting 6 inches above ground, marked 1 notch on the south and east edges.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, over a magnet, 24 inches in the ground, with aluminum cap marked:

T11S R3W
S26 | S25
S35 | S36
1999

Deposit the marked stone alongside the aluminum post.

Set a steel fence post alongside the corner.

Corner is located by corner of fences bearing E, W, and S.

From the corner of sections 25, 30, 31, and 36, east boundary, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 6 inches above ground, with brass cap marked as described in the official record of the 1987-90 resurvey of a portion of the west boundary of T. 11 S., R. 2 W.

N. 89° 45.8' W., between sections 25 and 36.

Over rolling land.

40.284 The 1/4 section corner of sections 25 and 36, monumented with a basalt stone 20x15x6 inches, firmly set, projecting 10 inches above ground, marked 1/4 on the north face.

At the corner point

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 11 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T11S R3W
1/4 S25
 S36
 1999

Deposit the marked stone alongside the aluminum post.

Set a steel fence post alongside the corner.

Corner is located 1 ft. north of an E and W fence line.

N. 89° 40.4' W., beginning new measurement.

40.366 The corner of sections 25, 26, 35, and 36.

N. 0° 01.0' W., between sections 25 and 26.

Over gentle rolling land.

30.000 Center line of old U.S. Highway No. 6, bears north and southwest.

40.332 Point for the 1/4 section corner of sections 25 and 26, at proportionate distance, falls in pavement of north bound lane of U.S. Highway No. 6; there is no remaining evidence of the original corner.

Set a mag nail, 1/4 inch diameter, flush with surface of road

from which

An aluminum post, 30 inches long, 2 1/2 inches diameter, over a magnet, 24 inches in the ground, for a reference monument, bears N. 81° 45.7' E., 97 1/2 links distance, with aluminum cap marked T11S R3W S25 RM 1999 and an arrow pointing to the corner.

An aluminum post, 30 inches long, 2 1/2 inches diameter, over a magnet, 24 inches in the ground, for a reference monument, bears N. 52° 50.7' W., 1.225 chains distance, with aluminum cap marked T11S R3W S26 RM 1999 and an arrow pointing to the corner.

80.664 Point for the corner of sections 23, 24, 25, and 26, at proportionate distance, falls in pavement of south bound lane of U.S. Highway No. 6; there is no remaining evidence of the original corner.

Set a mag nail, 1/4 inch diameter, flush with surface of road.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 11 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

from which

An aluminum post, 30 inches long, 2 1/2 inches diameter, over a magnet, 24 inches in the ground, for a reference monument, bears N. 36° 54.3' E., 1.18 chains distance, with aluminum cap marked T11S R3W S24 RM 1999 and an arrow pointing to the corner.

An aluminum post, 30 inches long, 2 1/2 inches diameter, over a magnet, 24 inches in the ground, for a reference monument, bears S. 87° 32.6' W., 87 1/2 links distance, with aluminum cap marked T11S R3W S26 RM 1999 and an arrow pointing to the corner.

From the corner of sections 19, 24, 25, and 30, east boundary, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 6 inches above ground, with brass cap marked as described in the official record of the 1987-90 resurvey of a portion of the west boundary of T. 11 S., R. 2 W.

S. 89° 57.2' W., between sections 24 and 25.

Over mountainous land.

40.528 Point for the 1/4 section corner of sections 24 and 25, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, over a magnet, 24 inches in the ground, with aluminum cap marked:

	T11S R3W
	<u>S24</u>
1/4	S25
	1999

Set a steel fence post alongside the aluminum post.

81.056 The corner of sections 23, 24, 25, and 26.

N. 0° 13.1' W., between sections 23 and 24.

Over nearly level land.

40.332 Point for the 1/4 section corner of sections 23 and 24, at proportionate distance, falls in the fill area of U.S. Highway No. 6; there is no remaining evidence of the original corner.

Set a bathay bar, 2 inches below surface.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 11 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

from which

An aluminum post, 30 inches long, 2 1/2 inches diameter, set over a magnet, 24 inches in the ground, for a reference monument, bears S. 89° 36.8' E., 1.555 chains distance, with aluminum cap marked T11S R3W S24 RM 1999 and an arrow pointing to the corner.

An aluminum post, 30 inches long, 2 1/2 inches diameter, set over a magnet, 24 inches in the ground, for a reference monument, bears N. 86° 48.9' W., 96 links distance, with aluminum cap marked T11S R3W S23 RM 1999 and an arrow pointing to the corner.

Corner is located 8 feet west of edge of pavement.

80.664

Point for the corner of sections 13, 14, 23, and 24, at proportionate distance, falls in the right of way of U.S. Highway No. 6; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, over a magnet, 24 inches in the ground, with aluminum cap marked:

T11S R3W	
S14	S13
S23	S24
1999	

from which

An aluminum post, 30 inches long, 2 1/2 inches diameter, set over a magnet, 24 inches in the ground, for a reference monument, bears N. 56° 06.6' E., 2.24 chains distance, with aluminum cap marked T11S R3W S13 RM 1999 and an arrow pointing to the corner.

An aluminum post, 30 inches long, 2 1/2 inches diameter, set over a magnet, 24 inches in the ground, for a reference monument, bears N. 43° 09.81' W., 1.05 chains distance, with aluminum cap marked T11S R3W S14 RM 1999 and an arrow pointing to the corner.

Corner is located 5 feet north of a draw, bears east and west.

From the corner of sections 13, 18, 19, and 24, east boundary, monumented with a steel post, 2 1/2 inches diameter, firmly set, projecting 6 inches above ground, with brass cap marked as described in the official record of the 1987-90 resurvey of a portion of the west boundary of T. 11 S., R. 2 W.

N. 89° 37.4' W., between sections 13 and 24.

Over rolling land.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 11 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS**40.742**

Point for the 1/4 section corner of sections 13 and 24, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, over a magnet, 24 inches in the ground, with aluminum cap marked:

T11S R3W
1/4 S13
 S24
 1999

Set a steel fence post alongside the aluminum post.

Corner is located 8 ft. west of a trail road and approximately 30 ft. NW of a water trough.

81.484

The corner of sections 13, 14, 23, and 24.

N. 0° 21.5' E., between sections 13 and 14.

Over nearly level land.

20.166

Point for the S 1/16 section corner of sections 13 and 14, falls in fill area of U.S. Highway No. 6.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, over a magnet, 24 inches in the ground, with aluminum cap marked:

S 1/16
S14 | S13
1999

from which

An aluminum post, 30 inches long, 2 1/2 inches diameter, set over a magnet, 24 inches in the ground, for a reference monument, bears N. 83° 39.5' E., 1.80 chains distance, with aluminum cap marked T11S R3W S13 RM 1999 and an arrow pointing to the corner.

An aluminum post, 30 inches long, 2 1/2 inches diameter, set over a magnet, 24 inches in the ground, for a reference monument, bears N. 47° 08.1' W., 93 links distance, with aluminum cap marked T11S R3W S14 RM 1999 and an arrow pointing to the corner.

Corner is located 32 feet west of the center line of U.S. Highway No. 6, bears N and S., and 69 feet east of right-of-way fence.

40.332

Point for the 1/4 section corner of sections 13 and 14, at proportionate distance; falls in fill area of U.S. Highway No. 6; there is no remaining evidence of the original corner.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 11 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, over a magnet, 24 inches in the ground, with aluminum cap marked:

T11S R3W
1/4
S14 | S13
1999

from which

An aluminum post, 30 inches long, 2 1/2 inches diameter, set over a magnet, 24 inches in the ground, for a reference monument, bears S. 77° 35.5' E., 1.345 chains distance, with aluminum cap marked T11S R3W S13 RM 1999 and an arrow pointing to the corner.

An aluminum post, 30 inches long, 2 1/2 inches diameter, set over a magnet, 24 inches in the ground, for a reference monument, bears N. 55° 19.4' W., 94 links distance, with aluminum cap marked T11S R3W S14 RM 1999 and an arrow pointing to the corner.

Corner is located 27 feet west of the center line of U.S. Highway No. 6, and 80 feet east of a right of way fence, bears N and S.

80.664

Point for the corner of sections 11, 12, 13, and 14, at proportionate distance, falls in fill area of U.S. Highway No. 6; there is no remaining evidence of the original corner.

Set a bathy bar, 2 inches below surface of ground.

from which

An aluminum post, 30 inches long, 2 1/2 inches diameter, set over a magnet, 24 inches in the ground, for a reference monument, bears S. 57° 04.6' E., 1.605 chains distance, with aluminum cap marked T11S R3W S13 RM 1999 and an arrow pointing to the corner.

An aluminum post, 30 inches long, 2 1/2 inches diameter, set over a magnet, 24 inches in the ground, for a reference monument, bears N. 89° 02.1' W., 1.05 chains distance, with aluminum cap marked T11S R3W S11 RM 1999 and an arrow pointing to the corner.

Corner is located 15 feet west of center line of U. S. Highway No. 6, and 90 feet east of right-of-way fence, bears N and S.

From the corner of sections 7, 12, 13, and 18, east boundary, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 6 inches above ground, with brass cap marked as described in the official record of the 1987-90 resurvey of a portion of the west boundary of T. 11 S., R. 3 W.

N. 89° 23.7' W., between sections 12 and 13.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 11 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Over rolling land.

40.125

Point for the 1/4 section corner of sections 12 and 13, determined by the corner of a fence projecting north, south, and west. There is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, over a magnet, 24 inches in the ground, with aluminum cap marked:

T11S R3W
1/4 S12
 S13
 1999

N. 89° 34.8' W., beginning new measurement.

40.799

The corner of sections 11, 12, 13, and 14.

N. 0° 25.9' E., between sections 11 and 12.

Over rolling land.

40.332

Point for the 1/4 section corner of sections 11 and 12, at proportionate distance, falls in paved road, U.S. Highway No. 6; there is no remaining evidence of the original corner.

At the corner point, set a mag nail, 1/4 inch diameter, flush with surface of road.

from which

An aluminum post, 30 inches long, 2 1/2 inches diameter, set over a magnet, 24 inches in the ground, for a reference monument bears N. 89° 29.0' E., 1.15 chains distance, with aluminum cap marked T11S R3W S12 RM 1999 and an arrow pointing to the corner.

An aluminum post, 30 inches long, 2 1/2 inches diameter, set over a magnet, 24 inches in the ground, for a reference monument, bears S. 89° 15.7' W., 1.25 chains distance, with aluminum cap marked T11S R3W S11 RM 1999 and an arrow pointing to the corner.

80.664

Point for the corner of sections 1, 2, 11, and 12, at proportionate distance, falls in pavement of U.S. Highway No. 6; there is no remaining evidence of the original corner.

At the corner point, set a mag nail, 1/4 inch diameter, flush with surface of road.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 11 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

from which

An aluminum post, 30 inches long, 2 1/2 inches diameter, set over a magnet, 24 inches in the ground, for a reference monument, bears S. 52° 25.3' W., 1.805 chains distance, with aluminum cap marked T11S R3W S11 RM 1999 and an arrow pointing to the corner.

An aluminum post, 30 inches long, 2 1/2 inches diameter, set over a magnet, 24 inches in the ground, for a reference monument, bears N. 51° 13.1' W., 1.852 chains distance, with aluminum cap marked T11S R3W S2 RM 1999 and an arrow pointing to the corner.

From this corner point, the corner of sections 1, 6, 7, and 12, west boundary, bears S. 89° 58.2' E., 80.134 chains distance, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 4 inches above ground, with brass cap marked as described in the official record of the 1987-90 resurvey of a portion of the west boundary of T. 11 S., R. 2 W.

N. 0° 01.8' E., between sections 1 and 2.

Over gentle rolling land.

25.103 Intersect line 2-3 of Cape Horn No. 10 lode, Mineral Survey No. 6997; not monumented.

27.664 Intersect line 4-5 of Cape Horn No. 10 lode, Mineral Survey No. 6997; not monumented.

40.330 Point for the 1/4 section corner of sections 1 and 2, at proportionate distance, falls in pavement of U.S. Highway No. 6; there is no remaining evidence of the original corner.

At the corner point, set a mag nail, 1/4 inch diameter, flush with surface of road.

from which

An aluminum post, 30 inches long, 2 1/2 inches diameter, set over a magnet, 24 inches in the ground, for a reference monument, bears N. 89° 55.6' E., 1.17 chains distance, with aluminum cap marked T11S R3W S1 RM 1999 and an arrow pointing to the corner.

An aluminum post, 30 inches long, 2 1/2 inches diameter, set over a magnet, 24 inches in the ground, for a reference monument, bears N. 83° 29.8' W., 1.395 chains distance, with aluminum cap marked T11S R3W S2 RM 1999 and an arrow pointing to the corner.

80.539 The standard corner of sections 1, 2, 35, and 36, north boundary, hereinbefore described.

From the corner of sections 2, 3, 34, and 35, south boundary, monumented with an aluminum post, 2 1/2 inches diameter, firmly set, projecting 6 inches above ground, with aluminum cap marked as described in the official record of the 1996-97 resurvey of a portion of the north boundary of T. 12 S., R. 3 W.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 11 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

N. $0^{\circ} 48.7'$ E., between sections 34 and 35.

Over rolling land.

40.613

Point for the $1/4$ section corner of sections 34 and 35, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 $1/2$ inches diameter, over a magnet, 24 inches in the ground, with aluminum cap marked:

T11S R3W
1/4
S34 | S35
1999

Set a steel fence post alongside the corner.

81.226

Point for the corner of sections 26, 27, 34, and 35, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 $1/2$ inches diameter, over a magnet, 24 inches in the ground, with aluminum cap marked:

T11S R3W
S27 | S26
S34 | S35
1999

Set a steel fence post alongside the corner.

From the corner of sections 25, 26, 35, and 36.

N. $89^{\circ} 40.5'$ W., between sections 26 and 35.

Over rolling land.

40.369

Point for the $1/4$ section corner of sections 26 and 35, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 $1/2$ inches diameter, over a magnet, 24 inches in the ground, with aluminum cap marked:

T11S R3W
1/4 S26
 S35
 1999

Set a steel fence post alongside the corner.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 11 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

80.738

The corner of sections 26, 27, 34, and 35.

N. 1° 04.3' W., between sections 26 and 27.

Over rolling land.

40.616

The 1/4 section corner of sections 26 and 27, monumented with a black lava stone, 12x10x4 inches, firmly set, projecting 8 inches above ground, dimly marked 1/4 on the west face.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, over a magnet, 24 inches in the ground, with aluminum cap marked:

T11S R3W
1/4
S27 | S26
1999

Deposit the dimly marked stone alongside the aluminum post.

Set a steel fence post alongside the corner.

N. 0° 07.3' W., beginning new measurement.

40.539

The corner of sections 22, 23, 26, and 27, monumented with a black lava stone, 18x8x6 inches, firmly set, projecting 12 inches above ground, marked 2 notches on the south and east edges.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, over a magnet, 24 inches in the ground, with aluminum cap marked:

T11S R3W
S22 | S23
S27 | S26
1999

Deposit the marked stone alongside the aluminum post.

Set a steel fence post alongside the corner.

From the corner of sections 23, 24, 25, and 26.

N. 89° 20.2' W., between sections 23 and 26.

Over rolling land.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 11 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

40.771

The 1/4 section corner of sections 23 and 26, monumented with a trachyte stone, 18x10x8 inches, firmly set, projecting 10 inches above ground, marked 1/4 on the north face.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, over a magnet, 14 inches in the ground to bedrock, and in a mound of stone, 3 1/2 ft. base, to top of aluminum cap marked:

T11S R3W
1/4 S23
 S26
 1999

Deposit the marked stone alongside the iron post.

Set a steel fence post alongside the corner.

N. 89° 20.4' W., beginning new measurement.

40.775

The corner of sections 22, 23, 26, and 27.

N. 0° 02.2' W., between sections 22 and 23.

Over rolling land.

40.534

The 1/4 section corner of sections 22 and 23, monumented with a lava stone, 12x8x6 inches, firmly set, projecting 8 inches above ground, marked 1/4 on the west face.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, over a magnet, 24 inches in the ground, with aluminum cap marked:

T11S R3W
1/4
S22 | S23
1999

Deposit the marked stone alongside the aluminum post.

Set a steel fence post alongside the corner.

N. 0° 08.1' W., beginning new measurement.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 11 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS**40.529**

The corner of sections 14, 15, 22, and 23, monumented with a limestone, 13x10x6 inches, firmly set, projecting 6 inches above ground, marked 3 notches on the south and 2 notches on the east edges.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, over a magnet, 24 inches in the ground, with aluminum cap marked:

T11S R3W	
<u>S15</u>	<u>S14</u>
S22	S23
1999	

Deposit the marked stone alongside the aluminum post.

Set a steel fence post alongside the corner.

From the corner of sections 13, 14, 23, and 24.

N. 89° 03.3' W., between sections 14 and 23.

Over rolling land.

40.674

Point for the 1/4 section corner of sections 14 and 23, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, over a magnet, 24 inches in the ground, with aluminum cap marked:

T11S R3W	
1/4	<u>S14</u>
	S23
1999	

Set a steel fence post alongside the corner.

81.348

The corner of sections 14, 15, 22, and 23.

N. 0° 05.8' W., between sections 14 and 15.

Over rolling land.

40.323

The 1/4 section corner of sections 14 and 15, monumented with a limestone, 10x8x8 inches, firmly set, projecting 5 inches above ground, marked 1/4 on the west face.

At the corner point

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 11 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, over a magnet, 24 inches in the ground, with aluminum cap marked:

T11S R3W
1/4
S15 | S14
1999

Deposit the marked stone alongside the aluminum post.

Set a steel fence post alongside the corner.

N. 0° 04.5' W., beginning new measurement.

40.166

The corner of sections 10, 11, 14, and 15, monumented with a white sandstone, 12x8x6 inches, firmly set, projecting 6 inches above ground, marked 4 notches on the south and 2 notches on the east edges.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, over a magnet, 24 inches in the ground, with aluminum cap marked:

T11S R3W
S10 | S11
S15 | S14
1999

Deposit the marked stone alongside the aluminum post.

Set a steel fence post alongside the corner.

From the corner of sections 11, 12, 13, and 14.

N. 89° 11.0' W., between sections 11 and 14.

Over rolling land.

40.977

Point for the 1/4 section corner of sections 11 and 14, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, over a magnet, 24 inches in the ground, with aluminum cap marked:

T11S R3W
1/4 S11
 S14
 1999

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 11 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Set a steel fence post alongside the corner.

81.954 The corner of sections 10, 11, 14, and 15.

N. 0° 36.2' E., between sections 10 and 11.

Over rolling land.

40.581 The 1/4 section corner of sections 10 and 11, monumented with a white sandstone, 12x8x8 inches, firmly set, projecting 5 inches above ground, marked 1/4 on the west face.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, over a magnet, 24 inches in the ground, with aluminum cap marked:

T11S R3W
1/4
S10 | S11
1999

Deposit the marked stone alongside the aluminum post.

Set a steel fence post alongside the corner.

N. 1° 58.7' E., beginning new measurement.

40.315 Point for the corner of sections 2, 3, 10, and 11, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, over a magnet, 24 inches in the ground, with aluminum cap marked:

T11S R3W
S3 | S2
S10 | S11
1999

Set a steel fence post alongside the corner.

From the corner of sections 1, 2, 11, and 12.

N. 89° 01.6' W., between sections 2 and 11.

Over rolling land.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 11 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS**40.364**

Point for the 1/4 section corner of sections 2 and 11, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, over a magnet, 24 inches in the ground, with aluminum cap marked:

T11S R3W
1/4 S2
 S11
 1999

Set a steel fence post alongside the corner.

80.728

The corner of sections 2, 3, 10, and 11.

N. 0° 48.0' W., between sections 2 and 3.

Over rolling land.

40.294

Point for the 1/4 section corner of sections 2 and 3, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, over a magnet, 24 inches in the ground, with aluminum cap marked:

T11S R3W
1/4
S3 | S2
1999

Set a steel fence post alongside the corner.

79.782

The closing corner of sections 2 and 3, on the north boundary of the township, hereinbefore described.

From the corner of sections 26, 27, 34, and 35.

S. 89° 47.8' W., between sections 27 and 34.

Over rolling land.

40.539

Point for the 1/4 section corner of sections 27 and 34, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, over a magnet, 24 inches in the ground, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 11 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

T11S R3W

1/4 S27
 S34
 1999

Set a steel fence post alongside the corner.

- 81.078** The corner of sections 27, 28, 33, and 34, monumented with an aluminum post, 2 1/2 inches diameter, firmly set, projecting 4 inches above ground, with aluminum cap marked as described in the official record of the 1996-97 resurvey of a portion of the subdivisional lines in T. 11 S., R. 3 W.

N. 0° 09.6' E., between sections 27 and 28.

Over rolling land.

- 40.840** The 1/4 section corner of sections 27 and 28, monumented with a granite stone, 11x10x10 inches, firmly set, projecting 5 inches above ground, dimly marked 1/4 on the west face.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, over a magnet, 24 inches in the ground, with aluminum cap marked:

T11S R3W

1/4
S28 | S27
1999

Deposit the marked stone alongside the aluminum post.

Set a steel fence post alongside the corner.

N. 0° 10.3' W., beginning new measurement.

- 40.580** Point for the corner of sections 21, 22, 27, and 28, determined by the corner of a fence, with fences extending north and west. There is no remaining evidence of the original corner.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, over a magnet, 24 inches in the ground, with aluminum cap marked:

T11S R3W

S21 | S22
S28 | S27
1999

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 11 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Set a steel fence post alongside the corner.

From the corner of sections 22, 23, 26, and 27.

S. 89° 59.4' W., between sections 22 and 27.

Over rolling land.

39.990

Point for the 1/4 section corner of sections 22 and 27, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, over a magnet, 24 inches in the ground, with aluminum cap marked:

T11S R3W
1/4 $\frac{S22}{S27}$
1999

Set a steel fence post alongside the corner.

59.985

Point for the W 1/16 section corner of sections 22 and 27.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, over a magnet, 24 inches in the ground, with aluminum cap marked:

T11S R3W
W 1/16 $\frac{S22}{S27}$
1999

Set a steel fence post alongside the corner.

79.980

The corner of sections 21, 22, 27, and 28.

N. 0° 06.6' E., between sections 21 and 22.

Over rolling land.

40.228

Point for the 1/4 section corner of sections 21 and 22, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, over a magnet, 24 inches in the ground, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 11 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

T11S R3W

1/4

S21 | S22

1999

Set a steel fence post alongside the corner.

60.342

Point for the N 1/16 section corner of sections 21 and 22.

This corner point is not monumented.

80.456

The corner of sections 15, 16, 21, and 22, monumented with a limestone, 16x8x6 inches, projecting 8 inches above ground, marked 3 notches on the south and east edges.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, over a magnet, 24 inches in the ground, with aluminum cap marked:

T11S R3W

S16 | S15

S21 | S22

1999

Deposit the marked stone alongside the aluminum post.

Set a steel fence post alongside the corner.

Corner is located by fence corner, with fences extending south and west.

From the corner of sections 14, 15, 22, and 23.

S. 89° 33.1' W., between sections 15 and 22.

Over rolling land.

39.844

Point for the 1/4 section corner of sections 15 and 22, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, over a magnet 24 inches in the ground, with aluminum cap marked:

T11S R3W

1/4 S15

S22

1999

Set a steel fence post alongside the corner.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 11 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

79.688

The corner of sections 15, 16, 21, and 22.

N. 0° 10.9' E., between sections 15 and 16.

Over rolling land.

40.363

The 1/4 section corner of sections 15 and 16, monumented with a granite stone, 16x12x10 inches, firmly set, projecting 8 inches above ground, marked 1/4 on the west face.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, over a magnet, 24 inches in the ground, with aluminum cap marked:

T11S R3W
1/4
S16 | S15
1999

Deposit the marked stone alongside the aluminum post.

Set a steel fence post alongside the corner.

Corner is located in old N and S fence line.

N 0° 10.1' E., beginning new measurement.

40.331

The corner of sections 9, 10, 15, and 16, monumented with a sandstone, 16x8x6 inches, firmly set, projecting 8 inches above ground, marked 4 notches on the south, and 3 notches on the east edges.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, over a magnet, 24 inches in the ground, with aluminum cap marked:

T11S R3W
S 9 | S10
S16 | S15
1999

Deposit the marked stone alongside the aluminum post.

Set a steel fence post alongside the corner.

From the corner of sections 10, 11, 14, and 15.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 11 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

S. 89° 41.9' W., between sections 10 and 15.

Over rolling land.

39.652

Point for the 1/4 section corner of sections 10 and 15, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, over a magnet, 24 inches in the ground, with aluminum cap marked:

T11S R3W
1/4 S10
 S15
 1999

Set a steel fence post alongside the corner.

79.304

The corner of sections 9, 10, 15, and 16.

N. 0° 01.6' E., between sections 9 and 10.

Over rolling land.

40.274

The 1/4 section corner of sections 9 and 10, monumented with a black granite stone, 10x8x8 inches, firmly set, projecting 6 inches above ground, marked 1/4 on the west face.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, over a magnet, 24 inches in the ground, with aluminum cap marked:

T11S R3W
1/4
S9 | S10
1999

Deposit the marked stone alongside the aluminum post.

Set a steel fence post alongside the corner.

N. 0° 37.2' E., beginning new measurement.

40.255

The corner of sections 3, 4, 9, and 10, monumented with a black granite stone, 12x8x6 inches, firmly set, projecting 6 inches above ground, marked 5 notches on the south and 3 notches on the east edges.

At the corner point

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 11 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, over a magnet, 24 inches in the ground, with aluminum cap marked:

T11S R3W

S4	S3
S9	S10

 1999

Deposit the marked stone alongside the aluminum post.

Set a steel fence post alongside the corner.

From the corner of sections 2, 3, 10, and 11.

S. 89° 27.6' W., between sections 3 and 10.

Over rolling land.

40.328

Point for the 1/4 section corner of sections 3 and 10, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, over a magnet, 24 inches in the ground, with aluminum cap marked:

T11S R3W
 1/4

S3	S10
----	-----

 1999

Set a steel fence post alongside the corner.

80.656

The corner of sections 3, 4, 9, and 10.

N. 0° 07.4' W., between sections 3 and 4.

Over rolling land.

40.320

The 1/4 section corner of sections 3 and 4, monumented with a limestone, 18x10x6 inches, firmly set, projecting 8 inches above ground, dimly marked 1/4 on the west face.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, over a magnet, 24 inches in the ground, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 11 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

T11S R3W

1/4

S4 | S3

1999

Deposit the marked stone alongside the aluminum post.

Set a steel fence post alongside the corner.

N. 1° 30.4' E., beginning new measurement.

40.063

The standard corner of sections 3, 4, 33, and 34, north boundary, hereinbefore described.

From the corner of sections 28, 29, 32, and 33, monumented with an aluminum post, 2 1/2 inches diameter, firmly set, projecting 4 inches above ground, with aluminum cap marked as described in the official record of the 1996-97 resurvey of a portion of the subdivisional lines.

N. 0° 17.6' E., between sections 28 and 29.

Over rolling land.

40.266

The 1/4 section corner of sections 28 and 29, monumented with a quartzite stone, 16x8x8 inches, firmly set, projecting 2 inches above ground, dimly marked 1/4 on the west face.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, over a magnet, 24 inches in the ground, with aluminum cap marked:

T11S R3W

1/4

S29 | S28

1999

Deposit the marked stone alongside the aluminum post.

Set a steel fence post alongside the corner.

N. 0° 28.9' E., beginning new measurement.

40.265

The corner of sections 20, 21, 28, and 29, monumented with a conglomerate stone, 14x7x6 inches, firmly set, projecting 8 inches above ground, marked 2 notches on the south, and 4 notches on the east edges.

At the corner point

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 11 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, over a magnet, 24 inches in the ground, with aluminum cap marked:

T11S R3W	
<u>S20</u>	<u>S21</u>
S29	S28
1999	

Deposit the marked stone alongside the aluminum post.

Set a steel fence post alongside the corner.

Corner is located 7 ft. north of fence corner, with fences bearing east, west, and south.

From the corner of sections 21, 22, 27, and 28.

S. 89° 24.9' W., between sections 21 and 28.

Over rolling land.

40.148

Point for the 1/4 section corner of sections 21 and 28, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, over a magnet, 24 inches in the ground, with aluminum cap marked:

	T11S R3W
1/4	<u>S21</u>
	S28
	1999

Set a steel fence post alongside the corner.

80.296

The corner of sections 20, 21, 28, and 29.

N. 0° 10.7' E., between sections 20 and 21.

Over rolling land.

40.522

Point for the 1/4 section corner of sections 20 and 21, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, over a magnet, 24 inches in the ground, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 11 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

T11S R3W

1/4

S20 | S21

1999

Set a steel fence post alongside the corner.

81.044

Point for the corner of sections 16, 17, 20, and 21, at proportionate distance; there is no remaining evidence of the original corner position.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, over a magnet, 24 inches in the ground, with aluminum cap marked:

T11S R3W

S17 | S16

S20 | S21

1999

Set a steel fence post alongside the corner.

From the corner of sections 15, 16, 21, and 22.

S. 89° 50.1' W., between sections 16 and 21.

Over rolling land.

20.170

Point for the E 1/16 section corner of sections 16 and 21.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, over a magnet, 24 inches in the ground, with aluminum cap marked:

T11S R3W

E 1/16 S16

S21

1999

Set a steel fence post alongside the corner.

40.340

Point for the 1/4 section corner of sections 16 and 21, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T11S R3W

1/4 S16

S21

1999

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 11 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Set a steel fence post alongside the corner.

80.680

The corner of sections 16, 17, 20, and 21.

N. 0° 26.3' E., between sections 16 and 17.

Over rolling land.

40.522

The 1/4 section corner of sections 16 and 17, monumented with a sandstone, 20x18x16 inches, firmly set, projecting 10 inches above ground, dimly marked 1/4 on the west face.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, over a magnet, 24 inches in the ground, with aluminum cap marked:

T11S R3W
1/4
S17 | S16
1999

Deposit the marked stone alongside the aluminum post.

Set a steel fence post alongside the corner.

N. 0° 15.6' W., beginning new measurement.

40.464

Point for the corner of sections 8, 9, 16, and 17, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, over a magnet, 24 inches in the ground, with aluminum cap marked:

T11S R3W
S8 | S9
S17 | S16
1999

Set a steel fence post alongside the corner.

From the corner of sections 9, 10, 15, and 16.

N. 89° 57.5' W., between sections 9 and 16.

Over rolling land.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 11 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS**40.392**

Point for the 1/4 section corner of sections 9 and 16, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, over a magnet, 24 inches in the ground, with aluminum cap marked:

T11S R3W
1/4 S9
 S16
 1999

Set a steel fence post alongside the corner.

80.784

The corner of sections 8, 9, 16, and 17.

N. 0° 10.9' E., between sections 8 and 9.

Over rolling land.

40.464

Point for the 1/4 section corner of sections 8 and 9, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, over a magnet, 24 inches in the ground, with aluminum cap marked:

T11S R3W
1/4
S8 | S9
1999

Set a steel fence post alongside the corner.

80.928

Point for the corner of sections 4, 5, 8, and 9, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, over a magnet, 24 inches in the ground, with aluminum cap marked:

T11S R3W
S5 | S4
S8 | S9
1999

Set a steel fence post alongside the corner.

From the corner of sections 3, 4, 9, and 10.

N. 89° 40.5' W., between sections 4 and 9.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 11 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Over rolling land.

40.482

Point for the 1/4 section corner of sections 4 and 9, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, over a magnet 24 inches in the ground, with aluminum cap marked:

T11S R3W
1/4 S4
 S9
 1999

Set a steel fence post alongside the corner.

80.964

The corner of sections 4, 5, 8, and 9.

N. 0° 11.0' W., between sections 4 and 5.

Over rolling land.

20.232

Point for the S 1/16 section corner of sections 4 and 5.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, over a magnet, 24 inches in the ground, with aluminum cap marked:

T11S R3W
S 1/16
S5 | S4
1999

Set a steel fence post alongside the corner.

40.464

Point for the 1/4 section corner of sections 4 and 5, at proportionate distance; there is no remaining evidence of the original corner.

T11S R3W
1/4
S5 | S4
1999

Set a steel fence post alongside the corner.

80.321

The closing corner of sections 4 and 5, on the north boundary of the township, hereinbefore described.

From the corner of sections 20, 21, 28, and 29.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 11 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

N. 89° 56.7' W., between sections 20 and 29.

Over rolling land.

40.729

The 1/4 section corner of sections 20 and 29, monumented with a quartzite stone, 12x8x6 inches, firmly set, projecting 5 inches above ground, dimly marked 1/4 on the north face.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, over a magnet, 24 inches in the ground, with aluminum cap marked:

T11S R3W
1/4 S20
 S29
 1999

Deposit the marked stone alongside the aluminum post.

Set a steel fence post alongside the corner.

N. 89° 49.2' W., beginning new measurement.

40.882

The corner of sections 19, 20, 29, and 30, monumented with an aluminum post, 2 1/2 inches diameter, firmly set, projecting 6 inches above ground, with aluminum cap marked as described in the official record of the 1996-97 resurvey of a portion of the subdivisional lines.

N. 0° 22.2' E., between sections 19 and 20.

Over rolling land.

39.979

Point for the 1/4 section corner of sections 19 and 20, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, over a magnet, 24 inches in the ground, with aluminum cap marked:

T11S R3W
1/4
S19 | S20
1999

Set a steel fence post alongside the corner.

79.958

The corner of sections 17, 18, 19, and 20, monumented with a limestone, 16x8x4 inches, firmly set, projecting 10 inches above ground, marked 3 notches on the south and 5 notches on the east edges.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 11 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, over a magnet, 24 inches in the ground, with aluminum cap marked:

T11S R3W

S18	S17
S19	S20

 1999

Deposit the marked stone alongside the aluminum post.

Set a steel fence post alongside the corner.

Corner is located 75 links north of wash, which drains southeast.

From the corner of sections 16, 17, 20, and 21.

S. 89° 21.0' W., between sections 17 and 20.

Over rolling land.

40.414

Point for the 1/4 section corner of sections 17 and 20, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, over a magnet, 24 inches in the ground, with aluminum cap marked:

T11S R3W
 1/4

S17	S20
-----	-----

 1999

Set a steel fence post alongside the corner.

80.828

The corner of sections 17, 18, 19, and 20.

S. 89° 43.2' E., between sections 18 and 19.

Over rolling land.

40.000

The 1/4 section corner of sections 18 and 19, monumented with a sandstone, 14x8x6 inches, firmly set, projecting 8 inches above ground, marked 1/4 on the north face.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, over a magnet, 24 inches in the ground, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 11 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

T11S R3W

1/4 S18
 S19
 1999

Deposit the marked stone alongside the aluminum post.

Set a steel fence post alongside the corner.

S. 89° 17.7' W., beginning new measurement.

- 40.051** The corner of sections 13, 18, 19, and 24, west boundary, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 4 inches above ground, with brass cap marked as described in the official record of the 1968 resurvey of the east boundary of T. 11 S., R. 4 W.
-

From the corner of sections 17, 18, 19, and 20.

N. 0° 36.7' E., between sections 17 and 18,

Over rolling land.

- 40.692** Point for the 1/4 section corner of sections 17 and 18, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, over a magnet, 24 inches in the ground, with aluminum cap marked:

T11S R3W
1/4
S18 | S17
1999

Set a steel fence post alongside the corner.

- 81.384** Point for the corner of sections 7, 8, 17, and 18, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, over a magnet, 24 inches in the ground, with aluminum cap marked:

T11S R3W
S7 | S8
S18 | S17
1999

Set a steel fence post alongside the corner.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 11 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

From the corner of sections 8, 9, 16, and 17.

S. 89° 37.5' W., between sections 8 and 17.

Over rolling land.

40.033

Point for the 1/4 section corner of sections 8 and 17, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, over a magnet, 24 inches in the ground, with aluminum cap marked:

T11S R3W
1/4 $\frac{S8}{S17}$
1999

Set a steel fence post alongside the corner.

80.066

The corner of sections 7, 8, 17, and 18.

S. 89° 13.1' W., between sections 7 and 18.

Over rolling land.

40.196

Point for the 1/4 section corner of sections 7 and 18, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, over a magnet, 24 inches in the ground, with aluminum cap marked:

T11S R3W
1/4 $\frac{S7}{S18}$
1999

Set a steel fence post alongside the corner.

80.835

The corner of sections 7, 12, 13, and 18, west boundary, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 4 inches above ground, with brass cap marked as described in the official record of the 1968 resurvey of the east boundary of T. 11 S., R. 4 W.

From the corner of sections 7, 8, 17, and 18.

N. 0° 04.1' W., between sections 7 and 8.

Over rolling land.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 11 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS**40.689**

Point for the 1/4 section corner of sections 7 and 8, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, over a magnet, 24 inches in the ground, with aluminum cap marked:

T11S R3W
1/4
S7 | S8
1999

Set a steel fence post alongside the corner.

81.378

Point for the corner of sections 5, 6, 7, and 8, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, over a magnet, 24 inches in the ground, with aluminum cap marked:

T11S R3W
S6 | S5
S7 | S8
1999

Set a steel fence post alongside the corner.

From the corner of sections 4, 5, 8, and 9.

S. 89° 56.9' W., between sections 5 and 8.

Over rolling land.

40.202

Point for the 1/4 section corner of sections 5 and 8, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, over a magnet 24 inches in the ground, with aluminum cap marked:

T11S R3W
1/4 S5
 S8
 1999

Set a steel fence post alongside the corner.

80.404

The corner of sections 5, 6, 7, and 8.

S. 89° 43.9' W., between sections 6 and 7.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 11 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Over rolling land.

40.354

Point for the 1/4 section corner of sections 6 and 7, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, over a magnet, 24 inches in the ground, with aluminum cap marked:

T11S R3W
1/4 S6
 S7
 1999

Set a steel fence post alongside the corner.

81.353

The corner of sections 1, 6, 7, and 12, west boundary, monumented with an iron post, 2 1/2 inches diameter, firmly set, 6 inches above ground, with brass cap marked as described in the official record of the 1968 resurvey of the east boundary of T. 11 S., R. 4 W.

From the corner of sections 5, 6, 7, and 8.

N. 0° 41.9' W., between sections 5 and 6.

Over rolling land.

20.346

Point for the S 1/16 section corner of sections 5 and 6.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, over a magnet, 24 inches in the ground, with aluminum cap marked:

T11S R3W
S 1/16
S6 | S5
1999

Set a steel fence post alongside the corner.

40.692

Point for the 1/4 section corner of sections 5 and 6, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, over a magnet, 24 inches in the ground, with aluminum cap marked:

T11S R3W
1/4
S6 | S5
1999

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 11 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Set a steel fence post alongside the corner.

80.814

The closing corner of sections 5 and 6, on the north boundary of the township, hereinbefore described.

The Subdivision of Section 3,
T. 11 S., R. 3 W., Salt Lake Meridian, Utah

From the 1/4 section corner of sections 3 and 10.

N. 0° 03.2' W., on the N-S center line of section 3.

Over rolling land.

40.308

Point for the center 1/4 section corner of section 3, at intersection with the E-W center line.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, over a magnet, 24 inches in the ground, with aluminum cap marked:

T11S R3W
C 1/4 S3
1999

Set a steel fence post alongside the corner.

79.926

The 1/4 section corner of section 3 only, north boundary, hereinbefore described.

From the 1/4 section corner of sections 2 and 3.

S. 89° 28.6' W., on the E-W center line of section 3.

Over rolling land.

39.798

The center 1/4 section corner of section 3.

80.171

The 1/4 section corner of sections 3 and 4.

The Subdivision of Section 5,
T. 11 S., R. 3 W. Salt Lake Meridian, Utah

From the 1/4 section corner of sections 5 and 8.

N. 0° 36.5' W., on the N-S center line of section 5.

THE SUBDIVISION OF SECTION 5,
T. 11 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Over rolling land.

20.288 Point for the center S 1/16 section corner of section 5.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, over a magnet, 24 inches in the ground, with aluminum cap marked:

T11S R3W
C
S 1/16 | S5
C
1999

Set a steel fence post alongside the corner.

40.576 Point for the center 1/4 section corner of section 5, at intersection with the E-W center line.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, over a magnet, 24 inches in the ground, with aluminum cap marked:

T11S R3W
C 1/4 S5
1999

Set a steel fence post alongside the corner.

80.498 The 1/4 section corner of section 5 only, north boundary, hereinbefore described.

From the 1/4 section corner of sections 4 and 5.

N. 89° 53.5' W., on the E-W center line of section 5.

Over rolling land.

40.381 The center 1/4 section corner of section 5.

80.760 The 1/4 section corner of sections 5 and 6.

From the S 1/16 section corner of sections 4 and 5.

N. 89° 58.3' W., on the E-W center line of the SE 1/4 of section 5.

Over rolling land.

40.291 The center S 1/16 section corner of section 5.

THE SUBDIVISION OF SECTION 5,
T. 11 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

N. $89^{\circ} 58.3'$ W., on the E-W center line of the SW $1/4$ of section 5.

Over rolling land.

40.290 The S $1/16$ section corner of sections 5 and 6.

The Subdivision of Section 13,
T. 11 S., R. 3 W. Salt Lake Meridian, Utah

From the $1/4$ section corner of sections 13 and 24.

N. $0^{\circ} 24.2'$ E., on the N-S center line of section 13.

Over rolling land.

20.186 Point for the center S $1/16$ section corner of section 13.

Set an aluminum post, 30 inches long, 2 $1/2$ inches diameter, over a magnet, 24 inches in the ground, with aluminum cap marked:

T11S R3W
C
S $1/16$ | S13
C
1999

Set a steel fence post alongside the corner.

Corner is located on west edge of N and S trail road.

40.372 Point for the center $1/4$ section corner of section 13, at intersection with the E-W center line.

Set an aluminum post, 30 inches long, 2 $1/2$ inches diameter, over a magnet, 16 inches in the ground to bedrock, in a mound of stone, 4 ft. base to top of aluminum cap marked:

T11S R3W
C $1/4$ S13
1999

Set a steel fence post alongside the corner.

81.233 The $1/4$ section corner of sections 12 and 13.

From the $1/4$ section corner of sections 13 and 18, east boundary, monumented with an iron post, 2 $1/2$ inches diameter, firmly set, projecting 4 inches above ground, with brass cap marked as described in the 1987-90 resurvey of a portion of the west boundary of T. 11 S., R. 2 W.

THE SUBDIVISION OF SECTION 13,
T. 11 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

N. 89° 40.7' W., on the E-W center line of section 13.

Over rolling land.

40.490 The center 1/4 section corner of section 13.

81.258 The 1/4 section corner of sections 13 and 14.

From the center S 1/16 section corner of section 13.

N. 89° 39.1' W., on the E-W center line of the SW 1/4 of section 13.

Over rolling land.

40.755 The S 1/16 section corner of sections 13 and 14.

The Subdivision of Section 16,
T. 11 S., R. 3 W. Salt Lake Meridian, Utah

From the 1/4 section corner of sections 16 and 21.

N. 0° 07.9' E., on the N-S center line of section 16.

Over rolling land.

40.442 Point for the center 1/4 section corner of section 16, at intersection with the E-W center line.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, over a magnet, 24 inches in the ground, with aluminum cap marked:

T11S R3W
C 1/4 S16
1999

Set a steel fence post alongside the corner.

80.840 The 1/4 section corner of sections 9 and 16.

From the 1/4 section corner of sections 15 and 16.

S. 89° 56.9' W., on the E-W center line of section 16.

Over rolling land.

40.371 The center 1/4 section corner of section 16.

THE SUBDIVISION OF SECTION 16,
T. 11 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

80.491 The 1/4 section corner of sections 16 and 17.

The Subdivision of Section 21,
T. 11 S., R. 3 W., Salt Lake Meridian, Utah

From the 1/4 section corner of sections 21 and 28.

N. $0^{\circ} 02.1'$ W., on the N-S center line of section 21.

Over rolling land.

40.374 Point for the center 1/4 section corner of section 21, at intersection with the E-W center line.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, over a magnet, 24 inches in the ground, with aluminum cap marked:

T11S R3W
C 1/4 S21
1999

Set a steel fence post alongside the corner.

60.561 Point for the center N 1/16 section corner of section 21.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, over a magnet, 24 inches in the ground, with aluminum cap marked:

T11S R3W
C
S 1/16 | S21
C
1999

Set a steel fence post alongside the corner.

80.748 The 1/4 section corner of sections 16 and 21.

From the 1/4 section corner of sections 21 and 22.

S. $89^{\circ} 37.5'$ W., on the E-W center line of section 21.

Over rolling land.

20.122 Point for the center E 1/16 section corner of section 21.

THE SUBDIVISION OF SECTION 21,
T. 11 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Corner point not monumented.

40.244 The center 1/4 section corner of section 21.

80.488 The 1/4 section corner of sections 20 and 21.

From the point for the center E 1/16 section corner of section 21.

N. 0° 02.3' E., on the N-S center line of the NE 1/4 of section 21.

Over rolling land.

20.150 Point for the NE 1/16 section corner of section 21, at intersection with the E-W center line of the NE 1/4.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, over a magnet, 24 inches in the ground, with aluminum cap marked:

T11S R3W
NE 1/16 S21
1999

Set a steel fence post alongside the corner.

40.300 The E 1/16 section corner of sections 16 and 21.

From the point for the N 1/16 section corner of sections 21 and 22.

S. 89° 43.8' W., on the E-W center line of the NE 1/4 of section 21.

Over rolling land.

20.146 The NE 1/16 section corner of section 21.

40.292 The center N 1/16 section corner of section 21.

The Subdivision of Section 22,
T. 11 S., R. 3 W., Salt Lake Meridian, Utah

From the 1/4 section corner of sections 22 and 27.

N. 0° 00.7' E., on the N-S center line of section 22.

Over rolling land.

THE SUBDIVISION OF SECTION 22,
T. 11 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS**40.381**

Point for the center 1/4 section corner of section 22, at intersection with the E-W center line.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, over a magnet, 24 inches in the ground, with aluminum cap marked:

T11S R3W
C 1/4 S22
1999

Set a steel fence post alongside the corner.

80.759

The 1/4 section corner of sections 15 and 22.

From the 1/4 section corner of sections 22 and 23.

S. 89° 46.2' W., on the E-W center line of section 22.

Over rolling land.

39.952

The center 1/4 section corner of section 22.

59.911

Point for the center W 1/16 section corner of section 22.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, over a magnet, 24 inches in the ground, with aluminum cap marked:

T11S R3W
C $\frac{W\ 1/16}{S22}$ C
1999

Set a steel fence post alongside the corner.

79.870

The 1/4 section corner of sections 21 and 22.

From the W 1/16 section corner of sections 22 and 27.

N. 0° 03.6' E., on the N-S center line of the SW 1/4 of section 22.

Over rolling land.

40.304

The center W 1/16 section corner of section 22.

The Subdivision of Section 35,
T. 11 S., R. 3 W., Salt Lake Meridian, Utah

THE SUBDIVISION OF SECTION 35,
T. 11 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

From the 1/4 section corner of sections 2 and 35, south boundary, monumented with an aluminum post, 2 1/2 inches diameter, firmly set, projecting 4 inches above ground, with aluminum cap marked as described in the official record of the 1996-97 resurvey of the north boundary of T. 12 S., R. 3 W.

N. 1° 03.6' E., on the N-S center line of section 35.

Over rolling land.

40.588 Point for the center 1/4 section corner of section 35, at intersection with the E-W center line.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, over a magnet, 24 inches in the ground, with aluminum cap marked:

T11S R3W
C 1/4 S35
1999

Set a steel fence post alongside the corner.

81.038 The 1/4 section corner of sections 26 and 35.

From the 1/4 section corner of sections 35 and 36.

N. 89° 54.6' W., on the E-W center line of section 35.

Over rolling land.

40.041 The center 1/4 section corner of section 35.

80.239 The 1/4 section corner of sections 34 and 35.

Dependent Resurvey of a Portion of Mineral Survey
No. 6997, T. 11 S., R. 3 W., Salt Lake Meridian, Utah

Reestablishment of the Survey by
Arthur A. Miller in 1929

Cape Horn No. 11 Lode (6997)

From corner No. 3, Cape Horn No. 11 lode, monumented with an iron post, 2 inches diameter, firmly set in concrete base, projecting 18 inches above ground, with cap marked as described in; Mineral Survey No. 6997 in 1929.

From this corner, the corner of sections 1, 2, 11, and 12, bears S. 38° 40.4' W., 14.717 chains distance.

DEPENDENT RESURVEY OF A PORTION OF MINERAL SURVEY
No. 6997, T. 11 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Thence

N. 34° 04.0' W., along line 3-4, Cape Horn No. 11 lode.

Over rolling land.

- 9.170** Point for corner No. 4, Cape Horn No. 11 lode, identical with corner No. 2 Cape Horn No. 10 lode, at proportionate distance, based on the Grant Boundary method; there is no remaining evidence of the original corner. Point not monumented.

Thence

N. 34° 04.4' W. along line 2-3, Cape Horn No. 10 lode.

- 6.370** Point for the witness corner to corner No. 3, Cape Horn No. 10 lode, at proportionate distance, based on the Grant Boundary method, falls in right-of-way of U.S. Highway No. 6; there is no remaining evidence of the original corner. Point not monumented.
- 7.252** Intersect the line between sections 1 and 2; not monumented.
- 7.356** The point for corner No. 3, Cape Horn No. 10 lode, at proportionate distance, based on the Grant Boundary method, falls in paved road, U.S. Highway No. 6; not monumented.

Thence

N. 0° 04.0' E., on line 3-4, Cape Horn No. 10 lode.

- 2.425** Point for corner No. 4, Cape Horn No. 10 lode, at record distance from witness corner of corner No. 4, falls in paved road, U.S. Highway No. 6; not monumented.

Thence

N. 48° 31.2' E., along line 4-5, Cape Horn No. 10 lode.

- 0.076** Intersect the line between sections 1 and 2; not monumented.
- 0.606** The witness corner for corner No. 4, Cape Horn No 10 lode, monumented with an iron post, 2 inches diameter, set in concrete base, projecting 18 inches above ground, with cap marked as described in Mineral Survey No. 6997 in 1929.
- 21.396** Corner No. 5, Cape Horn No. 10 lode, monumented with an iron post, 2 inches diameter, set in concrete base, projecting 18 inches above ground, with cap marked as described in Mineral Survey No. 6997 in 1929.

CERTIFICATE OF SURVEY

I, **Jerry L. Thomas, Cadastral Surveyor**, hereby certify upon honor that, in pursuance of special instructions bearing the date of the **9th day of August, 1999**, I have **executed a dependent resurvey of the north boundary (Second Standard Parallel South), a portion of the subdivisional lines, and a portion of Mineral Survey No. 6997, in sections 1 and 2, and the subdivision of sections 3, 5, 13, 16, 21, 22, and 35, in Township 11 South, Range 3 West,**

of the **Salt Lake Meridian**, in the State of **Utah**, which are represented in the foregoing field notes as having been executed by me and under my direction, and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

8/8/01
Date

Jerry L. Thomas
(Cadastral Surveyor)

Date

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Salt Lake City, Utah

The foregoing field notes of the **dependent resurvey of the north boundary (Second Standard Parallel South), a portion of the subdivisional lines, and a portion of Mineral Survey No. 6997, in sections 1 and 2, and the subdivision of sections 3, 5, 13, 16, 21, 22, and 35, in Township 11 South, Range 3 West**, executed by **Jerry L. Thomas, Cadastral Surveyor** having been critically examined and found correct, are hereby approved.

September 7, 2001
Date

Daniel W. Webb
(Chief Cadastral Surveyor for Utah)